

ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw ≥ 0.8 (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: **65 mm**

Maximum acoustic insulation: **Rw = 46 dBA**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class E1950

Wind resistance (EN 12210):

Class C5

Reference test: window 1.23 x 1.48 m / 2 sashes

SECTIONS	Frame 80 mm Sash 88 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 1.5 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: 45 mm
MAXIMUM DIMENSIONS	Width (L) = 1.500 mm Height (H) = 2.600 mm	GASKETS	EPDM triple gasket
MAXIMUM WEIGHT/SASH	160 Kg	FOAMS	Perimeter polyolefin foam in glazing rebate zone
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns	OPENING POSSIBILITIES	
	Wood effect powder coating According to Qualideco standard	INWARD	Side hung, tilt & turn, tilt & parallel, bottom hung
HARDWARE	Anodized According to Ewwa Euras Standard Class 15	OUTWARD	Side hung and top hung projecting
	Optionally Class 20 and 25		
	Optionally bicoloured		
AESTHETIC POSSIBILITIES	Sash: Straight Bead: Straight or curved		

